

## Customer Specification

### PART NO. 1892/3C

## Construction

						Diameter ("in")	
1) Component 1						3 x 1 COND	
a) Conductor						12 (65/30) AWG Tinned Copper	0.093
b) Insulation						0.020" Wall, Nom. PVC	0.133
(1) Color Code						Alpha Wire Color Code D	
Cond	Color	Cond	Color	Cond	Color		
1	BLACK	2	RED	3	WHITE		
2) Cable Assembly						3 Components Cabled	
a) Twists						2.8 Twists/foot (min.)	
b) Orientation						Components to be arranged from INSIDE LAYER-to-OUTSIDE LAYER	
3) Jacket						0.023" Wall, Nom. PVC	0.333 (0.349 max.)
a) Color(s)						SLATE	
b) Print						ALPHA WIRE-* P/N 1892/3C 3C 12 AWG (UL) 75C TYPE CL2 OR C(RU) AWM I/II A/B 80C 300V FT1 CE ROHS * = Factory Code	

## Applicable Specifications

1) UL	CL2	75°C
	VW-1	
2) CSA International	C(RU) AWM I/II A/B FT1	80°C / 300 V <sub>RMS</sub>
3) CE	EU Low Voltage Directive 2014/35/EU	

## Environmental

--

1) CE: EU Directive 2011/65/EU(RoHS2), EU Directive 2015/863/EU (RoHS3)	
	This product complies with European Directive 2011/65/EU (RoHS Directive) of the European Parliament and of the Council of 8 June 2011 and the amending Directive 2015/863/EU of 4 June 2015 . No Exemptions are required for RoHS Compliance on this item.
2) REACH Regulation (EC 1907/2006)	
	This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item.
3) California Proposition 65	This product may contain substances known to the State of California to cause Cancer or Reproductive Harm, but is exempt from labeling based on the Consent Judgement. See the Alpha Wire website for more detail.

## Properties

Physical & Mechanical Properties	
1) Temperature Range	-20 to 80°C
2) Bend Radius	10X Cable Diameter
3) Pull Tension	153 lbs. (max.)
Electrical Properties <i>(For Engineering purposes only)</i>	
1) Voltage Rating	300 V <sub>RMS</sub>
2) Capacitance	35 pF/ft @1 kHz, Nominal Conductor-to-Conductor
3) Inductance	0.16 µH/ft, Nominal
4) Conductor DCR	1.76 ω/1000ft @20°C, Nominal

## Other

Packaging	Flange x Traverse x Barrel (inches)
a) 1000 FT	18 x 14.25 x 8 Continuous Length
b) 500 FT	12 x 10.5 x 5 Continuous Length
c) 100 FT	10.5 x 5 x 3.5 Continuous Length
	<i>Spool dimensions may vary slightly.</i>

[www.alphawire.com](http://www.alphawire.com)

Alpha Wire  
2200 US Highway 27 South  
Richmond, IN 47374

Tel: 1-800-52 ALPHA

Although Alpha Wire (“Alpha”) makes every reasonable effort to ensure there accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha had been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

SpecPDFFooterConfidential



Alpha Wire □□□□1892/3C

[illegible]

Lead	□□□□□□□□□□0.1% (1000 ppm)
Mercury	□□□□□□□□□□0.1% (1000 ppm)
Cadmium	□□□□□□□□□□0.01% (100 ppm)
Hexavalent Chromium	□□□□□□□□□□0.1% (1000 ppm)
Polybrominated Biphenyls (PBB)	□□□□□□□□□□0.1% (1000 ppm)
Polybrominated Diphenyl Ethers (PBDE), Including Deca-BDE	□□□□□□□□□□0.1% (1000 ppm)
Bis(2-ethylhexyl) phthalate (DEHP)	□□□□□□□□□□0.1% (1000 ppm)
Butyl benzyl phthalate (BBP)	□□□□□□□□□□0.1% (1000 ppm)
Dibutyl phthalate (DBP)	□□□□□□□□□□0.1% (1000 ppm)
Diisobutyl phthalate (DIBP)	□□□□□□□□□□0.1% (1000 ppm)

Alpha Wire □□□□□□□□

DeBW

