



|--|--|--|--|--|--|

□□□ **2817/3**

Construction

						Diameters (In)	
1) Component 1					3 X 1 COND		
					20 (19/32) AWG Silver Plated Copper	0.040	
b) Insula	ation					0.009" Wall, Nom. PTFE	0.058
(1) Colo	r Code					Alpha Wire Color Code G	
Cond	Color	Cond	Color	Cond	Color	1	
1	WHITE	2	BLACK	3	RED		
2) Cable Assembly					3 Components Cabled		
a) Twists:					6.9 Twists/foot (min)		
b) Orientation:					Components to be arranged from INSIDE LAYER to OUTSIDE LAYER		
3) Shield					Silver Platted Copper BRAID Shield,90% Coverage, Min.		
4) Jacket					0.014" Wall, Nom.,PTFE Impregnated Fiberglass	0.180 (0.194 Max.)	
a) Color(s)					WHITE		
b) Jacket Separator					PTFE(skived) Tape, 25% Overlap, Min.		
		·	·	·			

Applicable Specifications

1) Military		
a) Component 1	MIL-W-16878/4 (Type E)	200°C / 600 V _{RMS}
2) Other		
a) Component 1	NEMA HP3-EXBGE	200°C / 600 V _{RMS}
3) CE:	EU Low Voltage Directive 2014/35/EU	
	•	

Environmental

1) CE: EU Directive 2011/65/EU(RoHS2), EU Directive 2015/863/EU (RoHS3):	
	This product complies with European Directive 2011/65/EU (RoHS Directive) of the European Parliament and of the Council of 8 June 2011 and the amending Directive 2015/863/EU of 4 June 2015. No Exemptions are required for RoHS Compliance on this item.
2) REACH Regulation (EC 1907/2006):	
	This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item.
3) California Proposition 65:	This product may contain substances known to the State of California to cause Cancer or Reproductive Harm, but is exempt from labeling based on the Consent Judgement. See the Alpha Wire website for more information.

Properties

Physical & Mechanical Properties			
1) Temperature Range	-55 to 200°C		
2) Bend Radius	10X Cable Diameter		
3) Pull Tension	33 Lbs, Maximum		
Electrical Properties	(For Engineering purposes only)		
1) Voltage Rating	600 V _{RMS}		
2) Capacitance	27 pF/ft @1 kHz, Nominal Conductor to Conductor		
3) Ground Capacitance	49 pF/ft @1 kHz, Nominal		
4) Inductance	0.16 μH/ft, Nominal		
5) Conductor DCR	8.8 Ω/1000ft @20°C, Nominal		
6) OA Shield DCR	5 Ω/1000ft @20°C, Nominal		

Other

Packaging	Flange x Traverse x Barrel (inches)	
a) 1000 FT	11 x 8.5 x 5 Max. 3 separate pieces; Min length/piece 100 FT.	
b) 100 FT	6.5 x 4 x 2.5 Continuous length	
	[Spool dimensions may vary slightly]	

www.alphawire.com

Alpha Wire 2200 US Highway 27 South Richmond, IN 47374

Tel: 1-800-52 ALPHA



Richmond, IN 47374
Tel: 1-800-52 ALPHA
Web: www.alphawire.com

	_	_	_	
_	_	_	_	

Alpha Wire □□□□2817/3

2817/3000RoHS0000 2005/7/1 000000

□□□□□□□□0.1% (1000 ppm) Lead Mercury □□□□□□□□0.01% (100 ppm) Cadmium Hexavalent Chromium □□□□□□□□0.1% (1000 ppm) Polybrominated Biphenyls (PBB) Polybrominated Diphenyl Ethers (PBDE), Including Deca-BDE Bis(2-ethylhexyl) phthalate (DEHP) □□□□□□□□0.1% (1000 ppm) Butyl benzyl phthalate (BBP) Dibutyl phthalate (DBP) □□□□□□□□0.1% (1000 ppm) Diisobutyl phthalate (DIBP) □□□□□□□□0.1% (1000 ppm)

Alpha Wire DDDDDDDD

□□□□□□□ Dave Watson 2025/12/1