

Customer Specification

PART NO. 3408

Construction

| | | | | | | Diameter ("in") | |
|-------------------|-------|------|--------|------|-------------|--|--------------------|
| 1) Component 1 | | | | | | 8 x 1 COND | |
| a) Conductor | | | | | | 18 (19/30) AWG Tinned Copper | 0.050 |
| b) Insulation | | | | | | 0.016" Wall, Nom. PVC | 0.082 |
| (1) Color Code | | | | | | Alpha Wire Color Code F | |
| Cond | Color | Cond | Color | Cond | Color | | |
| 1 | BLACK | 4 | GREEN | 7 | WHITE/BLACK | | |
| 2 | WHITE | 5 | ORANGE | 8 | RED/BLACK | | |
| 3 | RED | 6 | BLUE | | | | |
| 2) Cable Assembly | | | | | | 8 Components Cabled | |
| a) Twists | | | | | | 3.0 Twists/foot (min.) | |
| b) Orientation | | | | | | Components to be arranged from INSIDE LAYER-to-OUTSIDE LAYER | |
| c) Core Wrap | | | | | | Clear Mylar Tape, 25% Overlap (min.) | |
| 3) Shield | | | | | | Tinned Copper BRAID Shield,90% Coverage (min.) | |
| 4) Jacket | | | | | | 0.030" Wall, Nom. PVC | 0.364 (0.378 max.) |
| a) Color(s) | | | | | | SLATE | |
| b) Print | | | | | | ALPHA WIRE-* P/N 3408 CE ROHS * = Factory Code | |

Applicable Specifications

| | | |
|----------------|-------------------------------------|-------------------------------|
| 1) Military | | |
| a) Component 1 | MIL-W-16878/Type C | 105°C / 1000 V _{RMS} |
| 2) CE | EU Low Voltage Directive 2014/35/EU | |

Environmental

| | |
|---|---|
| 1) CE: EU Directive 2011/65/EU(RoHS2), EU Directive 2015/863/EU (RoHS3) | |
| | This product complies with European Directive 2011/65/EU (RoHS Directive) of the European Parliament and of the Council of 8 June 2011 and the amending Directive 2015/863/EU of 4 June 2015 . No Exemptions are required for RoHS Compliance on this item. |
| 2) REACH Regulation (EC 1907/2006) | |
| | This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item. |
| 3) California Proposition 65 | This product may contain substances known to the State of California to cause Cancer or Reproductive Harm, but is exempt from labeling based on the Consent Judgement. See the Alpha Wire website for more detail. |

Properties

| Physical & Mechanical Properties | |
|---|---|
| 1) Temperature Range | -55 to 105°C |
| 2) Bend Radius | 10X Cable Diameter |
| 3) Pull Tension | 129 lbs. (max.) |
| Electrical Properties | |
| <i>For Engineering purposes only</i> | |
| 1) Voltage Rating | 1000 V _{RMS} |
| 2) Capacitance | 44 pF/ft @1 kHz, Nominal Conductor-to-Conductor |
| 3) Ground Capacitance | 79 pF/ft @1 kHz, Nominal |
| 4) Inductance | 0.17 μH/ft, Nominal |
| 5) Conductor DCR | 5.9 ω/1000ft @20°C, Nominal |
| 6) OA Shield DCR | 2.7 ω/1000ft @20°C, Nominal |

Other

| Packaging | Flange x Traverse x Barrel (inches) |
|------------------|--|
| a) 1000 FT | 18 x 14.25 x 8 Continuous Length |
| b) 100 FT | 12 x 5.94 x 5 Continuous Length |
| | <i>Spool dimensions may vary slightly.</i> |

www.alphawire.com

Alpha Wire
2200 US Highway 27 South
Richmond, IN 47374

Tel: 1-800-52 ALPHA

Although Alpha Wire ("Alpha") makes every reasonable effort to ensure there accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha had been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

SpecPDFFooterConfidential

