



□□□ 55376

### **Construction**

						Diameters (In)	
1) Co	mponent 1					6 X 1 PAIR	
a) Co	nductor					18 (7/26) AWG Tinned Copper	0.048
b) Ins	ulation					0.010" Wall, Nom. FEP	0.068
(1) Cc	olor Code					Alpha Wire Color Code A	J
Pair	Color	Pair	Color	Pair	Color		
1	BLACK-RED	3	BLACK- GREEN	5	BLACK- BROWN		
2	BLACK- WHITE	4	BLACK- BLUE	6	BLACK- YELLOW		
c) Pai	r					2/Cond Cabled Together	
(1) Tv	vists:					6.0 Twists/foot (min)	
2) Cal	ble Assembly					6 Components Cabled	
a) Tw	ists:					2.4 Twists/foot (min)	
b) Orientation:					Components to be arranged from INSIDE LAYER to OUTSIDE LAYER		
c) Co	re Wrap					PTFE(skived) Tape, 25% Overlap, Min.	
3) Shi	ield:					Alum/Mylar Tape, 25% Overlap, Min.	
a) Foil Direction						Foil Facing In	
b) Drain Wire						18 (7/26) AWG Tinned Copper	
4) Jacket						0.027" Wall, Nom.,FEP	0.402 (0.420 Max.)
a) Tint Color(s)						Natural Tan, Slate, Black, Yellow, Orange, Blue, Green, Red, White	
b) Ripcord						Para-Aramid fiber(Kevlar, Twaron or equal)	
c) Marker Tape						ALPHA WIRE-* XTRAGUARD(R) 5 - 18 AWG SHIELDED 150C (UL) CMP OR AWM 20229 LLXXXXXX CSA CMP FT6 CE ROHS * = Factory Code [Note: Product may have c(UL) or CSA markings depending upon plant of manufacture.]	

## **Applicable Specifications**

1) UL	CMP	150°C	
	AWM/STYLE 20229	150°C / 300 V <sub>RMS</sub>	
2) CSA International	CMP	150°C	
	FT6		
3) CE:	EU Low Voltage Directive 2014/35/EU		

## **Environmental**

1) CE: EU Directive 2011/65/EU(RoHS2), EU Directive 2015/863/EU (RoHS3):	
	This product complies with European Directive 2011/65/EU (RoHS Directive) of the European Parliament and of the Council of 8 June 2011 and the amending Directive 2015/863/EU of 4 June 2015 . No Exemptions are required for RoHS Compliance on this item.
2) REACH Regulation (EC 1907/2006):	
	This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item.
3) California Proposition 65:	This product may contain substances known to the State of California to cause Cancer or Reproductive Harm, but is exempt from labeling based on the Consent Judgement. See the Alpha Wire website for more information.

# **Properties**

Physical & Mechanical Properties			
1) Temperature Range	-80 to 200°C		
2) Bend Radius	10X Cable Diameter		
3) Pull Tension	181 Lbs, Maximum		
Electrical Properties	(For Engineering purposes only)		
1) Voltage Rating	300 V <sub>RMS</sub>		
2) Mutual Capacitance	17.1 pF/ft @1 kHz, Nominal		
3) Ground Capacitance	31 pF/ft @1 kHz, Nominal		
4) Characteristic Impedance	86 Ω		
5) Inductance	0.16 μH/ft, Nominal		
6) Conductor DCR	6.5 Ω/1000ft @20°C, Nominal		
7) OA Shield DCR	3.9 Ω/1000ft @20°C, Nominal		

## Other

Packaging	Flange x Traverse x Barrel (inches)
a) Bulk(Made-to-order)	

#### www.alphawire.com

Alpha Wire 2200 US Highway 27 South Richmond, IN 47374

Tel: 1-800-52 ALPHA



Richmond, IN 47374
Tel: 1-800-52 ALPHA
Web: www.alphawire.com

	_	_	_	
_	_	_	_	

Alpha Wire □□□□55376

55376000RoHS0000 2005/8/1 000000

□□□□□□□□0.1% (1000 ppm) Lead Mercury □□□□□□□□0.01% (100 ppm) Cadmium Hexavalent Chromium □□□□□□□□0.1% (1000 ppm) Polybrominated Biphenyls (PBB) Polybrominated Diphenyl Ethers (PBDE), Including Deca-BDE Bis(2-ethylhexyl) phthalate (DEHP) □□□□□□□□0.1% (1000 ppm) Butyl benzyl phthalate (BBP) Dibutyl phthalate (DBP) □□□□□□□□0.1% (1000 ppm) Diisobutyl phthalate (DIBP) □□□□□□□□0.1% (1000 ppm)

Alpha Wire DDDDDDDD

□□□□□□□ Dave Watson 2025/11/25