

## Customer Specification

### PART NO. 7602F

## Construction

						Diameter ("in")	
1) Component 1						1 x 4 PAIR	
a) Conductor						24 (7/32) AWG Copper Alloy	0.024
b) Insulation						0.011" Wall, Nom. Polyplefin (PO)	0.046
(1) Color(s)							
Pair	Color	Pair	Color	Pair	Color		
1	BLUE - WHITE/BLUE	3	GREEN - WHITE/GREEN				
2	ORANGE - WHITE/ORANGE	4	BROWN - WHITE/BROWN				
c) Pair						2/Cond Cabled Together	
(1) Twists						13.7 Twists/ft. (approx.)	
d) Cabling						4 PAIR Cabled	
(1) Twists						3.0 Twists/ft. min.	
e) Jacket						0.020" Wall, Nom., TPE	0.254 (0.268 max.)
(1) Color(s)						WHITE	
2) Shield						Alum/Mylar Tape, 25% Overlap (min.)	
a) Foil Direction						Foil Facing Out	
b) Braid						Tinned Copper, 85% Coverage (min.)	
3) Jacket						0.030" Wall, Nom., TPE	0.342 (0.364 max.)
a) Color(s)						BLACK	
b) Ripcord						1300 1/E NATURAL POLYESTER	
c) Print						ALPHA WIRE-* P/N 7602F 4PR 24 AWG CONTINUOUS FLEX INDUSTRIAL ETHERNET (UL) C(UL) TYPE CM 75C FT1 ANSI/TIA-568-C.2 CAT5E PATCH VERIFIED CE ROHS (SEQ FOOTAGE) * = Factory Code <i>Note: Product may have c(UL) or CSA markings depending upon plant of manufacture.</i>	

## Applicable Specifications



Physical & Mechanical Properties	
1) Temperature Range	-40 to 80°C (static); -10 to 80°C (dynamic)
2) Bend Radius	8X Cable Diameter (static); 10X Cable Diameter (dynamic)
3) Pull Tension	40 lbs. max.
4) Sunlight Resistance	Yes
5) Cable Weight	60 lbs./1000ft.
6) Flex Life	10,000,000 Cycles
Electrical Properties	Engineering purposes only
1) Voltage Rating	300 V <sub>RMS</sub>
2) Characteristic Impedance	100 $\omega$ +/- 15
3) Mutual Capacitance	15 pf/ft.
4) Velocity of Propagation	69%
5) Conductor DCR	11 $\omega$ /100m (max.)
6) Skew	45 NS/100m (max.)
7) Pair to Ground Unbalance	330 pf/100m (max.)
8) DC Unbalance of a Pair	5% (max.)
9) Insertion Loss	2.5 (max. dB/100m) @ 1 MHz
	4.9 (max. dB/100m) @ 4 MHz
	6.9 (max. dB/100m) @ 8 MHz
	7.8 (max. dB/100m) @ 10 MHz
	9.9 (max. dB/100m) @ 16 MHz
	11.1 (max. dB/100m) @ 20 MHz
	12.5 (max. dB/100m) @ 25 MHz
	14.1 (max. dB/100m) @ 31.25 MHz
	20.4 (max. dB/100m) @ 62.5 MHz
	26.4 (max. dB/100m) @ 100 MHz

## Other

Packaging	Flange x Traverse x Barrel (inches)
a) 1000 FT	18 x 12 x 8 Continuous Length
b) 500 FT	16 x 11 x 8 Continuous Length
	<i>Spool dimensions may vary slightly.</i>

[www.alphawire.com](http://www.alphawire.com)

Alpha Wire  
2200 US Highway 27 South  
Richmond, IN 47374

Tel: 1-800-52 ALPHA

Although Alpha Wire ("Alpha") makes every reasonable effort to ensure there accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha had been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.



## EU/UK/China ROHS CERTIFICATE OF COMPLIANCE

To Whom It May Concern:

Alpha Wire Part Number: 7602F

7602F, RoHS-Compliant Commencing With 9/30/2013 Production

Note: all colors and put-ups

This document certifies that the Alpha part number cited above, including all packaging materials, is manufactured in accordance with Directive 2011/65/EU of the European Parliament, better known as the RoHS Directive (commonly known as RoHS 2), with regards to restrictions of the use of certain hazardous substances used in the manufacture of electrical and electronic equipment. This certification extends to amending Directive 2015/863/EU which expanded the list of restricted substances to 10 items (commonly known as RoHS 3). This product also complies with UK - RoHS. The reader is referred to these Directives for the specific definitions and extents of the Directives. **No Exemptions are required for RoHS Compliance on this item.** Additionally, Alpha certifies that the listed part number is in compliance with China RoHS "Marking for Control of Pollution by Electronic Information Products" standard SJ/T 11364-2014. This product is also in compliance with China RoHS 2 per GB/T 26572-2011.

### Substance

Substance	Maximum Control Value
Lead	0.1% by weight (1000 ppm)
Mercury	0.1% by weight (1000 ppm)
Cadmium	0.01% by weight (100 ppm)
Hexavalent Chromium	0.1% by weight (1000 ppm)
Polybrominated Biphenyls (PBB)	0.1% by weight (1000 ppm)
Polybrominated Diphenyl Ethers (PBDE) , Including Deca-BDE	0.1% by weight (1000 ppm)
Bis(2-ethylhexyl) phthalate (DEHP)	0.1% by weight (1000 ppm)
Butyl benzyl phthalate (BBP)	0.1% by weight (1000 ppm)
Dibutyl phthalate (DBP)	0.1% by weight (1000 ppm)
Diisobutyl phthalate (DIBP)	0.1% by weight (1000 ppm)

The information provided in this document and disclosure is correct to the best of Alpha Wire's knowledge, information and belief at the date of its release. The information provided is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it will become part of. The intent of this document is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Authorized Signatory for the Alpha Wire:

Dave Watson, Director of Engineering 8/2/2025

Alpha Wire  
2200 US Highway 27 South  
Richmond, IN 47374  
Tel: 1-908-925-8000