

Especificación de Cliente

NO. DE PIEZA 805032B

Construction

1) Construction	
a) Material	Nylon, high tenacity, continuous filament
b) Type	I
c) Size	3
d) Finish	E - Vinyl Chloride or Vinyl Chloride Acetate Copolymer, mercury and copper
e) Dimensions	0.085 +/- 0.009" x 0.014 +/- 0.003"
f) Color	Black

Applicable Specifications

1) Other	A-A-52080-E-3
	FED-STD-191

Environmental

--

1) EU Directive 2011/65/EU(RoHS2):	All materials used in the manufacture of this part meet the requirements of European Directive 2011/65/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment. No Exemptions are required for RoHS Compliance on this item. Consult Alpha Wire's web site for RoHS C of C .
2) REACH Regulation (EC 1907/2006):	This product does not contain any of the 16 substances listed on the European Union's REACH Substance of Very High Concern (SVHC) candidate list in excess of 0.1% mass of the item.
3) California Proposition 65:	The outer surface materials used in the manufacture of this part meet the requirements of California Proposition 65.

Properties

a) Breaking Strength	50 Lbs. Min.
b) Elongation	40% Max.
c) Finish Weight	15% - 30%
d) Temperature Range	-55°C to 121°C

Other

--

1) Standard Packaging	
a) 500 Yard Spools	Cardboard Tubes
b) Length Tolerance	+ 10/-3%
c) Multiple Lengths	4 lengths max per tube
	50 yard minimum individual length

www.alphawire.com

Alpha Wire
 2200 US Highway 27 South
 Richmond, IN 47374

Tel: 1-800-52 ALPHA

Aunque el Alambre Alfa ('Alfa') haga cada esfuerzo razonable para asegurar allí exactitud en el momento de publicación, información y especificaciones descritas aquí son sujetos a errores u omisiones y a cambios sin el aviso, y el listado de tal información y especificaciones no asegura la disponibilidad de producto.

La alfa proporciona la información y especificaciones aquí en un 'COMO ES' base, sin representaciones o garantías, si expreso, estatutario o implicado. Nunca va a Alfa ser obligado de cualquier daño (incluso consiguiente, indirecto, secundario, especial, punitivo, o ejemplar) independientemente de, aun si la Alfa hubiera sido informada de la posibilidad de tales daños, si en una acción conforme a contrato, negligencia o cualquier otra teoría, levantándose de o en relación al uso, o inhabilidad de usar, la información o especificaciones descrito aquí.

ALPHA WIRE - CONFIDENTIAL AND PROPRIETARY Notice to persons receiving this document and/or technical information. This document is confidential and is the exclusive property of ALPHA WIRE, and is merely on loan and subject to recall by ALPHA WIRE at any time. By taking possession of this document, the recipient acknowledges and agrees that this document cannot be used in any manner adverse to the interests of ALPHA WIRE, and that no portion of this document may be copied or otherwise reproduced without the prior written consent of ALPHA WIRE. In the case of conflicting contractual provisions, this notice shall govern the status of this document.

 ©2019 ALPHA WIRE - all rights reserved.



2200 US Highway 27 South
Richmond, IN 47374
Tel: 1-800-52 ALPHA
Web: www.alphawire.com

EU/China ROHS CERTIFICATE OF COMPLIANCE

To Whom It May Concern:

Alpha Wire Part Number: 805032B

805032B, RoHS-Compliant Commencing With 01/07/2005 Production

Note: all colors and put-ups

This document certifies that the Alpha part number cited above is manufactured in accordance with Directive 2011/65/EU of the European Union (RoHS 2), with regards to restrictions of the use of certain hazardous substances used in the manufacture of electrical and electronic equipment. The list of restricted substances to 10 items (commonly known as RoHS 3) The reader is referred to these Directives for the specific definitions and limits. **Compliance on this item.** Additionally, Alpha certifies that the listed part number is in compliance with China RoHS "Marking for Control"

Substance	Maximum Control Value
Lead	0.1% by weight (1000 ppm)
Mercury	0.1% by weight (1000 ppm)
Cadmium	0.01% by weight (100 ppm)
Hexavalent Chromium	0.1% by weight (1000 ppm)
Polybrominated Biphenyls (PBB)	0.1% by weight (1000 ppm)
Polybrominated Diphenyl Ethers (PBDE), Including Deca-BDE	0.1% by weight (1000 ppm)
Bis(2-ethylhexyl) phthalate (DEHP)	0.1% by weight (1000 ppm)
Butyl benzyl phthalate (BBP)	0.1% by weight (1000 ppm)
Dibutyl phthalate (DBP)	0.1% by weight (1000 ppm)
Diisobutyl phthalate (DIBP)	0.1% by weight (1000 ppm)

The information provided in this document and disclosure is correct to the best of Alpha Wire's knowledge, information and belief at the date of issuance. This document is intended to provide guidance for the safe handling, storage, and any other operation of the product itself or the one that it will become part of. The intent of this document is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulatory requirements. Authorized Signatory for the Alpha Wire:

Dave Watson, Director of Engineering & QA 04/06/2026

Alpha Wire
711 Lidgerwood Ave.
Elizabeth, NJ 07207
Tel: 1-908-925-8000