



Customer Specification

PART NO. 812030W

Construction	
1) Construction	
a) Material	9 Ply Round Polyester, high tenacity, continuous filament
b) Finish	Microcrystalline fungicide wax, mercury and copper free
c) Dimensions	0.045 " nominal
d) Color	White
I	

Applicable Specifications

1) Other	FED-STD-191	

Environmental

1) EU Directive 2011/65/EU(RoHS2):	
	All materials used in the manufacture of this part meet the requirements of European Directive 2011/65/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment. No Exemptions are required for RoHS Compliance on this item. Consult Alpha Wire's web site for RoHS C of C.
2) REACH Regulation (EC 1907/2006):	
	This product does not contain any of the 16 substances listed on the European Union's REACH Substance of Very High Concern (SVHC) candidate list in excess of 0.1% mass of the item.
3) California Proposition 65:	The outer surface materials used in the manufacture of this part meet the requirements of California Proposition 65.

Properties

a) Breaking Strength	150 Lbs. Min.
b) Elongation	15% Max.
c) Finish Weight	17% - 27%
d) Temperature Range	-73°C to 177°C

Standard Packaging	
a) Half Pound Spools 175 Yards per Pound	Cardboard Tubes
b) Length Tolerance	+10/-3%
c) Multiple Lengths	4 lengths max per tube
	50 yard minimum individual length

www.alphawire.com

Alpha Wire 2200 US Highway 27 South Richmond, IN 47374

Tel: 1-800-52 ALPHA

Although Alpha Wire ("Alpha") makes every reasonable effort to ensure there accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha had been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

SpecPDFFooterConfidential



Alpha Wire □□□□812030W

812030WDDDRoHSDDDD 2005/7/1 DDDDDD

Lead Mercury □□□□□□□□0.1% (1000 ppm) Cadmium Hexavalent Chromium □□□□□□□□0.1% (1000 ppm) Polybrominated Biphenyls (PBB) □□□□□□□□0.1% (1000 ppm) Polybrominated Diphenyl Ethers (PBDE), □□□□□□□□0.1% (1000 ppm) Including Deca-BDE Bis(2-ethylhexyl) phthalate (DEHP) Butyl benzyl phthalate (BBP) Dibutyl phthalate (DBP) □□□□□□□□0.1% (1000 ppm) Diisobutyl phthalate (DIBP)

Alpha Wire DDDDDDDDD

ППППППП Dave Watson 2025/9/16