2200 US Highway 27 South
Richmond, IN 47374
Tel: 1-800-52 ALPHA
Web: www.alphawire.com

□□□□□

□□□ FIT-221L-3/64

Construction

1) Tubing Type	Heat Shrinkable Tubing
2) Tubing Material	LSZH Polyolefin
3) Minimum Supplied ID(In)	0.046
4) Maximum Recovered ID (In)	0.023
5) Nominal Recovered Wall Thickness(In)	0.013
6) Color(s)	BLACK

Applicable Specifications

1) UL	Standard 224	125°C / 600 V_{RMS}
	VW-1	

Environmental

Properties

Physical & Mechanical Properties		
1) Temperature Range	-55 to 125°C	
2) Shrink Ratio	Approximately 2:1	
3) Full Recovery Temperature	110°C	
4) Minimum Shrink Temperature	100°C	
5) Tensile Strength	1500psi, Min	ASTM D638
6) Elongation	200%, Min	ASTM D638
7) Low Temperature Flex(-30°C)	no cracking	AMS-DTL-23053
8) Heat Resistance(158°C,168hrs)	100% Elongation, Min	ASTM D638
9) Heat Shock(250°C,4hrs)	no cracking	AMS-DTL-23053
10) Secant Modulus	$2.5x10^4$ psi, Min	ASTM D882
11) Longitudinal Change	+/-5%	AMS-DTL-23053
12) Shelf Life	25 Years @ 18 to 35°C	
Electrical Properties		
Chemical Properties		
1) Water Absorption	0.70%, Max	ASTM D570
2) Copper stability(158°C,168hrs)	100% Elongation, Min	UL 224
3) Corrosion(158°C,16hrs)	no corrosion	AMS-DTL-23053
4) Halogen Free	Yes	
5) Lead Free	Yes	

Other

Packaging	
1) 1000 FT	CR19-0.7: 19.75 x 0.75 x 8 Max. 3 pieces/Min length 125 FT.

www.alphawire.com

Alpha Wire
2200 US Highway 27 South
Richmond, IN 47374

Tel: 1-800-52 ALPHA

□□Alpha Wire□"Alpha"□□□□□□□□□□□□□□□□□□□□□□ □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□Alpha□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□Alpha□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ □□□□□

ALPHA WIRE - CONFIDENTIAL AND PROPRIETARY Notice to persons receiving this document and/or technical information. This document is confidential and is the exclusive property of ALPHA WIRE, and is merely on loan and subject to recall by ALPHA WIRE at any time. By taking possession of this document, the recipient acknowledges and agrees that this document cannot be used in any manner adverse to the interests of ALPHA WIRE, and that no portion of this document may be copied or otherwise reproduced without the prior written consent of ALPHA WIRE. In the case of conflicting contractual provisions, this notice shall govern the status of this document.

©2019 ALPHA WIRE - all rights reserved.

2200 US Highway 27 South
Richmond, IN 47374
Tel: 1-800-52 ALPHA
Web: www.alphawire.com

□□□□□

□□□□

Alpha Wire □□□□FIT-221L-3/64

FIT-221L-3/64□□□RoHS□□□□ 2014/1/27 □□□□□□

□□□□□□□□□□ *Alpha* □□□□□□□□□□□□□□□□□□□□□*2003□1□27□□2002/95/EC*□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□*RoHS*□□□□□□□□□□□□□□□□□□

□□□□	□□□□□
□	□□□□□□□□□□0.1% (1000 ppm)
□	□□□□□□□□□□0.1% (1000 ppm)
□	□□□□□□□□□□0.01% (100 ppm)
□□□	□□□□□□□□□□0.1% (1000 ppm)
□□□□ (PBB)	□□□□□□□□□□0.1% (1000 ppm)
□□□□□ (PBDE)	
□□□□□	□□□□□□□□□□0.1% (1000 ppm)

Alpha Wire □□□□□□□□□□□□□□□□□□□□

□□□□□□□□ Dave Watson 2026/6/5