

Customer Specification

PART NO. FIT-600-1-1/4

Construction

1) Tubing Type	Heat Shrinkable Tubing
2) Tubing Material	Chlorinated Polyolefin
3) Minimum Supplied ID(In)	1.250
4) Maximum Recovered ID (In)	0.714
5) Nominal Recovered Wall Thickness(In)	0.087
6) Color(s)	BLACK

Applicable Specifications

1) Other	AMS-DTL-23053/1 Class 1 and 2	
	Flammability - Passes	

Environmental

1) EU Directive 2011/65/EU(RoHS2):	All materials used in the manufacture of this part are in compliance with European Directive 2011/65/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment. Consult Alpha Wire's web site for RoHS C of C .
2) REACH Regulation (EC 1907/2006):	This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item. For up-to-date information, please see Alpha's REACH SVHC Declaration .
3) California Proposition 65:	The outer surface materials used in the manufacture of this part meet the requirements of California Proposition 65.

Properties

Physical & Mechanical Properties		
1) Temperature Range	-75 to 121°C	
2) Shrink Ratio	Approximately 2:1	
3) Full Recovery Temperature	130°C	
4) Minimum Shrink Temperature	130°C	
5) Tensile Strength	1500psi, Min	ASTM D638
6) Elongation	250%, Min	ASTM D638
7) Low Temperature Flex(-75°C)	no cracking	AMS-DTL-23053
8) Heat Resistance(150°C,168hrs)	200% Elongation, Min	ASTM D638
9) Heat Shock(200°C,4hrs)	no cracking	AMS-DTL-23053
10) Longitudinal Change	+1%/-10%	AMS-DTL-23053
11) Specific Gravity	1.30, Max	ASTM D792
12) Shelf Life	1 Years @ 18 to 35°C	
Electrical Properties		
1) Dielectric Strength	300 V/mil, Min	ASTM D876
2) Volume Resistivity	1x10 ¹¹ ohm-cm, Min	ASTM D876
Chemical Properties		
1) Water Absorption	1.00%, Max	ASTM D570
2) Corrosion(150°C,16hrs)	no corrosion	AMS-DTL-23053
3) Fluid Resistance(23°C,24 Hrs)	1000 PSI, Min	AMS-DTL-23053
4) Fungus Resistance	Pass	AMS-DTL-23053
5) Halogen Free	No	
6) Lead Free	Yes	

Other

Packaging
100 FT, 25 FT

www.alphawire.com

Alpha Wire
2200 US Highway 27 South
Richmond, IN 47374

Tel: 1-800-52 ALPHA

Although Alpha Wire (“Alpha”) makes every reasonable effort to ensure there accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an “AS IS” basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha had been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

SpecPDFFooterConfidential



EU/China ROHS CERTIFICATE OF COMPLIANCE

To Whom It May Concern:

Alpha Wire Part Number: FIT-600-1-1/4

FIT-600-1-1/4, RoHS-Compliant Commencing With 01/03/2006 Production

Note: all colors and put-ups

This document certifies that the Alpha part number cited above is manufactured in accordance with Directive 2011/65/EU of the European Union (2011/65/EU), with regards to restrictions of the use of certain hazardous substances used in the manufacture of electrical and electronic equipment. The list of restricted substances to 10 items (commonly known as RoHS 3) The reader is referred to these Directives for the specific definitions and **Compliance on this item**. Additionally, Alpha certifies that the listed part number is in compliance with China RoHS "Marking for Control"

Substance

Lead
Mercury
Cadmium
Hexavalent Chromium
Polybrominated Biphenyls (PBB)
Polybrominated Diphenyl Ethers (PBDE) ,
Including Deca-BDE
Bis(2-ethylhexyl) phthalate (DEHP)
Butyl benzyl phthalate (BBP)
Dibutyl phthalate (DBP)
Diisobutyl phthalate (DIBP)

Maximum Control Value

0.1% by weight (1000 ppm)
0.1% by weight (1000 ppm)
0.01% by weight (100 ppm)
0.1% by weight (1000 ppm)
0.1% by weight (1000 ppm)

0.1% by weight (1000 ppm)
0.1% by weight (1000 ppm)
0.1% by weight (1000 ppm)
0.1% by weight (1000 ppm)
0.1% by weight (1000 ppm)

The information provided in this document and disclosure is correct to the best of Alpha Wire's knowledge, information and belief at the date of this document. This document is intended to be used as a guide for the safe handling, storage, and any other operation of the product itself or the one that it will become part of. The intent of this document is to provide Regulatory information for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulatory requirements. Authorized Signatory for the Alpha Wire:

A handwritten signature in blue ink, appearing to read 'QBW', with a long horizontal line extending to the right.

Dave Watson, Director of Engineering & QA 31/08/2025

Alpha Wire
711 Lidgerwood Ave.
Elizabeth, NJ 07207
Tel: 1-908-925-8000