

# **Customer Specification**

## **PART NO. GRP-170-1/4**

### **Construction**

1) Tubing Type	Expandable Sleeving	
2) Tubing Material	Flame Retardant PolyPhenylene Sulfide (PPS)	
3) Minimum Supplied ID(In)	0.125	
4) Maximum Expanded ID (In)	0.375	
5) Nominal Wall Thickness +/- 0.005(In)	0.024	
6) Number of Carriers	48	
7) Number of Yarns	2	
8) Total Number of Monofilaments	96	
9) Color(s)	BLACK	

## **Applicable Specifications**

1) UL	UL-94 V0	
2) Other	FAR 25	

#### **Environmental**

Environmental				

1) EU Directive 2011/65/EU(RoHS2), EU Directive 2015/863/EU (RoHS3):	
	All materials used in the manufacture of this part are in compliance with European Directive 2011/65/EU and the amending Directive 2015/863/EU of 4 June 2015 regarding the restriction of use of certain hazardous substances in electrical and electronic equipment.
2) REACH Regulation (EC 1907/2006):	
	This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item.
3) California Proposition 65:	Exempt from warning labels based on the Consent Judgment. Please see Alpha's CA Prop 65 Statement for more information.

### **Properties**

Physical & Mechanical Properties			
1) Temperature Range	-70 to 200°C		
2) Specific Gravity	1.37, Max	ASTM D792	
<b>Electrical Properties</b>			
<b>Chemical Properties</b>			
1) Water Absorption	0.02%, Max	ASTM D570	
2) Corrosion(0°C,16hrs)	no corrosion	AMS-DTL-23053	
3) Fungus Resistance	Pass	AMS-DTL-23053	
4) Halogen Free	Yes		
5) Lead Free	Yes		

#### **Other**

Packaging			
1) 500 FT	CR6.5-6:	6.5 x 6 x 3.25	Max. 3 pieces/Min length 20 FT.

#### www.alphawire.com

Alpha Wire 2200 US Highway 27 South Richmond, IN 47374

Tel: 1-800-52 ALPHA

Although Alpha Wire ("Alpha") makes every reasonable effort to ensure there accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha had been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. SpecPDFFooterConfidential



### **EU/China ROHS CERTIFICATE OF COMPLIANCE**

To Whom It May Concern:

Alpha Wire Part Number: GRP-170-1/4

GRP-170-1/4, RoHS-Compliant Commencing With 24/09/2010 Production

Note: all colors and put-ups

This document certifies that the Alpha part number cited above is manufactured in accordance with Directive 2011/65/EU of the European 2), with regards to restrictions of the use of certain hazardous substances used in the manufacture of electrical and electronic equipment. T the list of restricted substances to 10 items (commonly known as RoHS 3) The reader is referred to these Directives for the specific definitio **Compliance on this item**. Additionally, Alpha certifies that the listed part number is in compliance with China RoHS "Marking for Control c

Substance	<b>Maximum Control Value</b>
Lead	0.1% by weight (1000 ppm)
Mercury	0.1% by weight (1000 ppm)
Cadmium	0.01% by weight (100 ppm)
Hexavalent Chromium	0.1% by weight (1000 ppm )
Polybrominated Biphenyls (PBB)	0.1% by weight (1000 ppm)
Polybrominated Diphenyl Ethers (PBDE) ,	
Including Deca-BDE	0.1% by weight (1000 ppm)
Bis(2-ethylhexyl) phthalate (DEHP)	0.1% by weight (1000 ppm)
Butyl benzyl phthalate (BBP)	0.1% by weight (1000 ppm)
Dibutyl phthalate (DBP)	0.1% by weight (1000 ppm)
Diisobutyl phthalate (DIBP)	0.1% by weight (1000 ppm)

The information provided in this document and disclosure is correct to the best of Alpha Wire's knowledge, information and belief at the diguide for the safe handling, storage, and any other operation of the product itself or the one that it will become part of. The intent of this context Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulatory for the Alpha Wire:

Dave Watson, Director of Engineering & QA 25/08/2025

Alpha Wire 711 Lidgerwood Ave. Elizabeth, NJ 07207 Tel: 1-908-925-8000