

Especificación de Cliente

NO. DE PIEZA GRP-200-3/8

Construction

1) Tubing Type	Expandable Sleeving
2) Tubing Material	Braided Perfluoroalkoxy
3) Minimum Supplied ID(In)	0.250
4) Maximum Expanded ID (In)	0.750
5) Nominal Wall Thickness +/- 0.005(In)	0.040
6) Number of Carriers	40
7) Number of Yarns	3
8) Total Number of Monofilaments	120
9) Color(s)	NATURAL

Applicable Specifications

1) Other	FAR 25	
----------	--------	--

Environmental

1) EU Directive 2011/65/EU(RoHS2), EU Directive 2015/863/EU (RoHS3):	All materials used in the manufacture of this part are in compliance with European Directive 2011/65/EU and the amending Directive 2015/863/EU of 4 June 2015 regarding the restriction of use of certain hazardous substances in electrical and electronic equipment.
2) REACH Regulation (EC 1907/2006):	This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item.
3) California Proposition 65:	Exempt from warning labels based on the Consent Judgment. Please see Alpha's CA Prop 65 Statement for more information.

Properties

Physical & Mechanical Properties		
1) Temperature Range	-70 to 280°C	
2) Specific Gravity	2.15, Max	ASTM D792
Electrical Properties		
Chemical Properties		
1) Water Absorption	0.01%, Max	ASTM D570
2) Corrosion(0°C,16hrs)	no corrosion	AMS-DTL-23053
3) Fungus Resistance	Pass	AMS-DTL-23053
4) Vacuum Outgassing - CVCM	95.00%, Max	ASTM E595
5) Halogen Free	No	
6) Lead Free	Yes	

Other

Packaging	
1) 250 FT	CR10.5-6: 10.5 x 6 x 3.25 Max. 3 pieces/Min length 20 FT.

www.alphawire.com

Alpha Wire
 2200 US Highway 27 South
 Richmond, IN 47374

Tel: 1-800-52 ALPHA

Aunque el Alambre Alfa ('Alfa') haga cada esfuerzo razonable para asegurar allí exactitud en el momento de publicación, información y especificaciones descritas aquí son sujetos a errores u omisiones y a cambios sin el aviso, y el listado de tal información y especificaciones no asegura la disponibilidad de producto.

La alfa proporciona la información y especificaciones aquí en un 'COMO ES' base, sin representaciones o garantías, si expreso, estatutario o implicado. Nunca va a Alfa ser obligado de cualquier daño (incluso consiguiente, indirecto, secundario, especial, punitivo, o ejemplar) independientemente de, aun si la Alfa hubiera sido informada de la posibilidad de tales daños, si en una acción conforme a contrato, negligencia o cualquier otra teoría, levantándose de o en relación al uso, o inhabilidad de usar, la información o especificaciones descrito aquí.

ALPHA WIRE - CONFIDENTIAL AND PROPRIETARY Notice to persons receiving this document and/or technical information. This document is confidential and is the exclusive property of ALPHA WIRE, and is merely on loan and subject to recall by ALPHA WIRE at any time. By taking possession of this document, the recipient acknowledges and agrees that this document cannot be used in any manner adverse to the interests of ALPHA WIRE, and that no portion of this document may be copied or otherwise reproduced without the prior written consent of ALPHA WIRE. In the case of conflicting contractual provisions, this notice shall govern the status of this document.

 ©2019 ALPHA WIRE - all rights reserved.



2200 US Highway 27 South
Richmond, IN 47374
Tel: 1-800-52 ALPHA
Web: www.alphawire.com

EU/China ROHS CERTIFICATE OF COMPLIANCE

To Whom It May Concern:

Alpha Wire Part Number: GRP-200-3/8

GRP-200-3/8, RoHS-Compliant Commencing With 24/09/2010 Production

Note: all colors and put-ups

This document certifies that the Alpha part number cited above is manufactured in accordance with Directive 2011/65/EU of the European Union (RoHS 2), with regards to restrictions of the use of certain hazardous substances used in the manufacture of electrical and electronic equipment. The list of restricted substances to 10 items (commonly known as RoHS 3) The reader is referred to these Directives for the specific definitions and **Compliance on this item**. Additionally, Alpha certifies that the listed part number is in compliance with China RoHS "Marking for Control"

Substance

Lead
Mercury
Cadmium
Hexavalent Chromium
Polybrominated Biphenyls (PBB)
Polybrominated Diphenyl Ethers (PBDE),
Including Deca-BDE
Bis(2-ethylhexyl) phthalate (DEHP)
Butyl benzyl phthalate (BBP)
Dibutyl phthalate (DBP)
Diisobutyl phthalate (DIBP)

Maximum Control Value

0.1% by weight (1000 ppm)
0.1% by weight (1000 ppm)
0.01% by weight (100 ppm)
0.1% by weight (1000 ppm)
0.1% by weight (1000 ppm)
0.1% by weight (1000 ppm)
0.1% by weight (1000 ppm)
0.1% by weight (1000 ppm)
0.1% by weight (1000 ppm)
0.1% by weight (1000 ppm)

The information provided in this document and disclosure is correct to the best of Alpha Wire's knowledge, information and belief at the date of issuance. This document is intended to provide guidance for the safe handling, storage, and any other operation of the product itself or the one that it will become part of. The intent of this document is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulatory requirements. Alpha Wire is not responsible for any regulatory information. Authorized Signatory for the Alpha Wire:

Dave Watson, Director of Engineering & QA 16/06/2026

Alpha Wire
711 Lidgerwood Ave.
Elizabeth, NJ 07207
Tel: 1-908-925-8000