

Customer Specification

PART NO. M3845

Construction

						Diameters (In)	
1) Component 1						2 X 1 COND	
a) Conductor						14 (7/.0242) AWG Bare Copper	0.073
b) Insulation						0.016" Wall, Nom. PVC/ 0.005" Wall NYLON	0.115
(1) Color Code						Alpha Wire Color Code J	
Cond	Color	Cond	Color	Cond	Color		
1	BLACK	2	RED				
2) Cable Assembly						2 Components run parallel under jacket.	
3) Jacket						0.047" Wall, Nom.,PVC	0.212X0.327
						(0.222X0.341 Max.)	
a) Color(s)						BLACK	
b) Print						ALPHA WIRE-* P/N M3845 2C 14 AWG EXXXXXX (UL) TYPE TC 600V 90C DRY 75C WET SUN RES DIR BUR CE ROHS * = Factory Code	

Applicable Specifications

1) UL	TC	90°C Dry / 75°C Wet / 600 V _{RMS}
	SUN RES	
	DIRECT BURIAL	
2) CE:	EU Low Voltage Directive 2014/35/EU	

Environmental

--

1) CE: EU Directive 2011/65/EU(RoHS2), EU Directive 2015/863/EU (RoHS3):	
	This product complies with European Directive 2011/65/EU (RoHS Directive) of the European Parliament and of the Council of 8 June 2011 and the amending Directive 2015/863/EU of 4 June 2015 . No Exemptions are required for RoHS Compliance on this item.
2) REACH Regulation (EC 1907/2006):	
	This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item.
3) California Proposition 65:	This product may contain substances known to the State of California to cause Cancer or Reproductive Harm, but is exempt from labeling based on the Consent Judgement. See the Alpha Wire website for more information.

Properties

Physical & Mechanical Properties	
1) Temperature Range	-25 to 90°C
2) Bend Radius	10X Cable Diameter
3) Pull Tension	64 Lbs, Maximum
4) Sunlight Resistance	Yes
5) Direct Burial	Yes
Electrical Properties	(For Engineering purposes only)
1) Voltage Rating	600 V _{RMS}
2) Capacitance	29 pF/ft @1 kHz, Nominal Conductor to Conductor
3) Characteristic Impedance	68 Ω
4) Inductance	0.17 μH/ft, Nominal
5) Conductor DCR	2.6 Ω/1000ft @20°C, Nominal

Other

Packaging	Flange x Traverse x Barrel (inches)
a) 1000 FT	13.5 x 10 x 4 Continuous length
b) 500 FT	11 x 8.5 x 5 Continuous length
c) 100 FT	10.5 x 5 x 3.5 Continuous length
d) Bulk(Made-to-order)	
	<i>[Spool dimensions may vary slightly]</i>

www.alphawire.com

Alpha Wire
2200 US Highway 27 South
Richmond, IN 47374

Tel: 1-800-52 ALPHA

Although Alpha Wire ("Alpha") makes every reasonable effort to ensure the accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha had been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

SpecPDFFooterConfidential



Alpha Wire □□□□M3845

☐ Alpha ☐ 2011/65/EU ☐ RoHS2 ☐ 2015/863/EU
RoHS ☐ SJ/T 11364-2014

Lead	□□□□□□□□□□0.1% (1000 ppm)
Mercury	□□□□□□□□□□0.1% (1000 ppm)
Cadmium	□□□□□□□□□□0.01% (100 ppm)
Hexavalent Chromium	□□□□□□□□□□0.1% (1000 ppm)
Polybrominated Biphenyls (PBB)	□□□□□□□□□□0.1% (1000 ppm)
Polybrominated Diphenyl Ethers (PBDE), Including Deca-BDE	□□□□□□□□□□0.1% (1000 ppm)
Bis(2-ethylhexyl) phthalate (DEHP)	□□□□□□□□□□0.1% (1000 ppm)
Butyl benzyl phthalate (BBP)	□□□□□□□□□□0.1% (1000 ppm)
Dibutyl phthalate (DBP)	□□□□□□□□□□0.1% (1000 ppm)
Diisobutyl phthalate (DIBP)	□□□□□□□□□□0.1% (1000 ppm)

Alpha Wire □□□□□□□□



