



□□□ XS-200N-1/8

## **Construction**

1) Tubing Type	Non-Expandable Sleeving	
2) Tubing Material	Braided Nylon	
3) Minimum Supplied ID(In)	0.125	
4) Nominal Wall Thickness +/- 0.005(In)	0.020	
5) Number of Carriers	28	
6) Number of Yarns	3	
7) Total Number of Monofilaments	84	
8) Color(s)	BLACK	
	`	

# **Applicable Specifications**

1) Military	MIL-S-47053	
2) Other	CID AA-59301	

### **Environmental**

1) EU Directive 2011/65/EU(RoHS2):		
	All materials used in the manufacture of this part are in compliance with European Directive 2011/65/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment. Consult Alpha Wire's web site for ROHS C of C.	
2) REACH Regulation (EC 1907/2006):		
	This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item. For up-to-date information, please see <u>Alpha's REACH SVHC Declaration</u> .	
3) California Proposition 65:	The outer surface materials used in the manufacture of this part meet the requirements of California Proposition 65.	

### **Properties**

1) Temperature Range	-45 to 120°C	
2) Tensile Strength	80000psi, Min	ASTM D638
3) Specific Gravity	1.14, Max	ASTM D792
Electrical Properties		
1) Dielectric Strength	4 V/mil, Min	ASTM D876
Chemical Properties		·
1) Water Absorption	0.04%, Max	ASTM D570
2) Corrosion(0°C,16hrs)	no corrosion	AMS-DTL-23053
3) Fungus Resistance	Pass	AMS-DTL-23053
4) Halogen Free	Yes	
5) Lead Free	Yes	

#### **Other**

Packaging	
100 FT	

#### www.alphawire.com

Alpha Wire 2200 US Highway 27 South Richmond, IN 47374

Tel: 1-800-52 ALPHA

ALPHA WIRE - CONFIDENTIAL AND PROPRIETARY Notice to persons receiving this document and/or technical information. This document is confidential and is the exclusive property of ALPHA WIRE, and is merely on loan and subject to recall by ALPHA WIRE at any time. By taking possession of this document, the recipient acknowledges and agrees that this document cannot be used in any manner adverse to the interests of ALPHA WIRE, and that no portion of this document may be copied or otherwise reproduced without the prior written consent of ALPHA WIRE. In the case of conflicting contractual provisions, this notice shall govern the status of this document. <br/>
'> colored ALPHA WIRE - all rights reserved.



Richmond, IN 47374
Tel: 1-800-52 ALPHA
Web: www.alphawire.com

	_	_	_	
_	_	_	_	

Alpha Wire □□□□XS-200N-1/8

XS-200N-1/8000RoHS0000 2006/1/16 000000

□□□□□□□□0.1% (1000 ppm) Lead Mercury □□□□□□□□0.01% (100 ppm) Cadmium Hexavalent Chromium □□□□□□□□0.1% (1000 ppm) □□□□□□□□0.1% (1000 ppm) Polybrominated Biphenyls (PBB) Polybrominated Diphenyl Ethers (PBDE), Including Deca-BDE Bis(2-ethylhexyl) phthalate (DEHP) □□□□□□□□0.1% (1000 ppm) Butyl benzyl phthalate (BBP) Dibutyl phthalate (DBP) □□□□□□□□0.1% (1000 ppm) Diisobutyl phthalate (DIBP) □□□□□□□□0.1% (1000 ppm)

Alpha Wire DDDDDDDD

□□□□□□□ Dave Watson 2025/10/28